Cabinet Lights Slim Pucks

Project:	Location:		Type:
Model Number	Oh	Noton	Data















Overview

	150
Light source	LED
Watts (W)	2.2W
Voltage	12V/24V
Lumen output (LM)	170LM
Efficiency (LM/W)	77LM/W
Color temperature (K)	2700K, 3000K, 4000K, 5000K
CRI	80CRI, 90CRI

GLI-CLSP

Cabinet Lights Slim Pucks

The GoLED Cabinet Lights Slim Pucks are specifically designed to provide task and accent lighting. These lights serve as the perfect addition to a diverse range of residential and commercial decors. They are particularly well-suited for enhancing the ambiance of kitchens, wine racks, wine cellars, bar counters, workbenches, hutches, bookcases, and shelves. With their sleek and compact design, the GoLED Cabinet Lights Slim Pucks effortlessly elevate the aesthetic appeal of any space while providing focused and stylish illumination.

Features and Specifications

- Aluminum alloy housing with PMMA diffuser
- Small form 3" diameter with 1/4" thickness
- 130lm/W luminous efficacy
- Small form puck wattage 2.2W(170LM)
- Color Temperatures: 2700K, 3000K, 4000K, 5000K
- Color Rendering Index (CRI): 80CRI and 90CRI
- 12V/24V, separate driver required
- PWM Dimmable

Certifications

- cFTLus Classified
- IP40
- Insulated ceiling

Warranty


- 5 years warranty
- Lifespan(LM70) of over 50 000 hours



Cabinet Lights Slim Pucks

DIMENSIONS

Small Form (SF)



ACCESSORIES

Item	Description		
000	Round magnetic trim		
	Hand Wave Module		
	Touch and Dimming Module		

Item	Description
	One to Six Hub
	Driver
	DC12V Wall Plug Adapter



Cabinet Lights Slim Pucks

SPECIFICATIONS

CODE	DIMENSIONS	WATTAGE	LUMENS	LUMENS/WATT	CRI	RATED LIFETIME
GLI-CLSP	3" x 1/4"	2.2W	170LM	77LM/W	80	50 000 hours

ORDERING GUIDE

SERIES	DIMENSIONS/WATTAGE	DRIVER	CCT	CRI	FINISH
GLI-CLSP					
	SF - Small 3" x 1/4" 2.2W	D12 - 12V 24W	27K - 2700K	80 - 80CRI	WH - White
		D22 - 24V 24W	30K - 3000K	90 - 90CRI	BK - Black
		D16 - 12V 60W	40K - 4000K		BN - Brushed nickel
		D26 - 24V 60W	50K - 5000K		
		WP - Wall plug			

ACCESSORIES

APPEND REQUIRED CODES

WM - Hand wave module

TM - Touch and Dimming Module

6H - Six port hub

